

# Gima S.p.A. Via Marconi, 1 - 20060 Gessate (MI) Italy gima@gimaitaly.com - export@gimaitaly.com www.gimaitaly.com

# TEST STERILIZZAZIONE TIPO 6 TYPE 6 EMULATING STEAM STRIPS

**ATTENZIONE:** Gli operatori devono leggere e capire completamente questo manuale prima di utilizzare il prodotto. **ATTENTION:** The operators must carefully read and completely understand the present manual before using the product.

#### PRODUCT NAME

IS 2601 Emulating Indicator Strips - Class 6.

# PRODUCT DESCRIPTION

PMS Steri-test Class 6 indicator strips, having a dimension of 25 mm x 60 mm with heat and steam sensitive ink, are printed on white carton, film coated. Indicator signs have triangle shape with rounded corners, 3 items arranged in a line. Indicator ink turns into reference color after an effective complete cycle. Strips are in Class 6 category according to ISO 11140-1 standard.

### **PURPOSE**

PMS Steri-test Class 6 indicator strips operate by means of color change and indicate that the loads have been exposed to sterilization process or not. They also have a function of indicating the conformity of sterilization conditions, (considering possible incorrect packaging, improper loading of the device and device failures).

# **APPLICATION**

- 1. Place min. one indicator strip for each sterilization pack. Placing the strip to a location where the steam reaches difficultly, helps you get better results.
- Place the sample into the sterilization device, operate the device at 134°C 3,5 minutes or at 121°C 15
  minutes in accordance with operation instruction.
- 3. Remove the indicator and observe the color changes after a complete operation cycle.
- 4. Operation cycle is successful, if the indicator color reaches the reference color or darker.
- 5. Operation cycle is insufficient, if the indicator color is lighter than reference color.

#### WARNINGS

Use of biological and mechanical indicators, besides chemical indicators, are recommended to validate the effectiveness of sterilization.

#### STORAGE CONDITIONS

Store at max. 35°C, dry place, and 70% RH max. The product has a shelf life of 3 years when stored at recommended conditions. No special storage conditions are necessary after sterilization.



Simboli - Symbols					
	Data di fabbricazione Date of manufacture	REF	Codice prodotto Product code	촟	Conservare al riparo dalla luce solare Keep away from sunlight
À	Leggere e seguire attentamente le istruzioni per l'uso Read instructions carefully	LOT	Numero di lotto Lot number	<del>*</del>	Conservare in luogo fresco ed asciutto Keep in a cool, dry place
$\subseteq$	Data di scadenza (vedi scatola / bustina) Expiration date (see box / package)	(2)	Dispositivo monouso, non riutilizzare Disposable device, do not re-use	38°C	Limite superiore di temperatura Upper limit of temperature
% %	Limite umidità Moisture limitation				

REF 35955 / IS2601

Fabbricato da/Manufactured by: PMS TIP TEKNOLOJILERI SANAYÌ VE TÌCARET A.Ş. Mersin Tarsus Organize Sanayi Bölgesi 12. Cad.No:2 33020 Mersin/TURKEY Made in Turkey









